

## ORIGINALS

## Savannah Extra Wide



**Packaging** 

Boards per pack: 4 boards m² per pack: 2,288 m<sup>2</sup> 19 kg Weight per pack:

Broken lenghts per pack: 25% minimal 60 cm length 40

Packs on a pallet:

**Dimensions** 

Length: 220 cm Width: 26 cm Thickness (total): 15 mm 3,5-4,0 mm Top layer:

Dimensional tolerances according to EN14342

Length: 0.20% Width: 0,2 mm

Total: 15 mm ± 0,2 mm Thickness:

3,5-4,0 mm Top layer: Height difference between the panels: ≤0,2 mm

Squareness: ≤0.2% across the width ≤0.2% across the width Cup: Spring: ≤0.1% over the length Bend: ≤1% over the length

Other Specifications

Release of formaldehyde: E1 HCHO Reaction to fire: Dfl-s1 Insulation value: R=0,11m2 k/w Brinell hardness: Average HB 3.7

Additional specifications

Bevel: 1 mm Construction: 3-layer 7% +/- 2% Moisture content: Dropdown Click Locking system:

## Instructions and Maintenance

Does not need to be oiled directly after installation. Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).

