

ORIGINALS

Savannah Extra Wide



Packaging

Boards per pack: 4 boards m² per pack: 2,288 m² Weight per pack: 19 kg

Broken lenghts per pack: 25% minimal 60 cm length

Packs on a pallet: 40

Dimensions

Length:220 cmWidth:26 cmThickness (total):15 mmTop layer:3,5-4,0 mm

Dimensional tolerances according to EN14342

Length: 0,20% Width: 0,2 mm

Thickness: Total: 15 mm \pm 0,2 mm

Top layer: 3,5-4,0 mm Height difference between the panels: ≤0,2 mm

Squareness: ≤0.2% across the width
Cup: ≤0.2% across the width
Spring: ≤0.1% over the length
Bend: ≤1% over the length

Other Specifications

Release of formaldehyde: E1 HCHO
Reaction to fire: Dfl-s1
Insulation value: R=0,11m2 k/w
Brinell hardness: Average HB 3.7

Additional specifications

Bevel: 1 mm

Construction: 3-layer

Moisture content: 7% +/- 2%

Locking system: Dropdown Click

Instructions and Maintenance

Does not need to be oiled directly after installation.

Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).

